

13.3 RIMS

NOMINAL TYRE SECTION WIDTH	APPROVED RIM CONTOURS		
Normal Section Sizes			
8 and 8.5	5.25	6.00	6.75
9 and 9.5	6.00	6.75	
10	6.75	7.50	
11	7.50	8.25	
12	8.25	9.00	
13	9.00	9.75	
'45' Series			
315	9.75		
355	11.75		
415	13.00	14.00	
455	14.00	15.00	
435	14.00	15.00	
495	16.00	17.00	
'50' Series			
355	11.75		
375	11.75	12.25	
445	14.00	15.00	
'55' Series			
265	8.25		
295	9.00	9.75	
385	11.75	12.25	
455	14.00	15.00	
'60' Series			
265	7.50	8.25	
285	8.25	9.00	
295	9.00	9.75	
305	9.00	9.75	
315	9.00	9.75	
555	16.00	17.00	
'65' Series			
385	11.75	12.25	
425	12.25	13.00	14.00
445	13.00	14.00	
525	16.00		
'70', '75', '80' and '90' Series			
205	5.25	6.00	6.75
215	6.00	6.75	
225	6.00	6.75	
235	6.75	7.50	
245	6.75	7.50	
255	6.75	7.50	8.25
265/70	6.75	7.50	
265	6.75	7.50	8.25
275	7.50	8.25	
285	7.50	8.25	9.00
295	8.25	9.00	
305	8.25	9.00	
315	9.00	9.75	
365	11.75		
375	11.75		
445	13.00	14.00	
605	18.00		

Notes: pages C.2-C.5.

Notes	Notes	Hinweise
The measuring rim widths are shown in bold.	Les largeurs de jante de mesure apparaissent en gras.	Die Messfelgen-Breiten stehen in Fettdruck.